DATA SHEET

FC *ADAPTER*253 / 297 / 298 Series



The SENKO FC Adapter Range is crafted to meet various applications and needs. With its plated metal housing and Zirconia split alignment sleeves, the FC Adapter provides a robust and dependable option for all your FC connectivity requirements. The Senko FC Adapters are available in three mounting styles: Square, Oval, and Round, with either a 2-hole or D-Style fixing. Additionally, these adapters offer both narrow and wide keyways to accommodate diverse requirements.

FEATURES

- Threaded coupling
- Integrated keyway
- Square, oval and round options
- Narrow and wide key way options
- Durable metal plated body
- 2 hole or D-style mounting
- Zirconia split alignment sleeve

APPLICATIONS

- Telecommunications
- Data centers
- Test and measurement equipment
- · Industrial applications
- · Medical equipment
- Military and aerospace
- Broadcast
- Medical equipment

KEY BENEFITS

- **✓** Secure and reliable connection
- **✓** High repeatability
- **✓** Highly stable performance
- **✓** Low IL and RL performance
- **✓** Simple installation
- **✓** Environmental resistance

Mechanical Data

	Value
Durability	200 matings per GR-326-Core
Fixing Method	2 hole screw fixing (square and oval), D style panel nut fixing (round)
Housing Material	Plated metal
Alignment Sleeve Material	Zirconia
Fiber Count	Simplex (1 channel)

Optical Data


	Value
Typical Insertion Loss (dB)*	0.10
Max Insertion Loss (dB)*	0.20


 $^{^* \}textit{Based on master grade jumper to low loss random mating test}$

Environmental Data

	Value
Operating Temperature	-40°C to +75°C
RoHS Compliance	Yes
REACH Compliance	Yes
Humidity Resistance	95%

Adapter Drawing









sales@senko.com 1-858-623-3300 senko.com/contact