

# **SN®UNBOOT**CONNECTOR

# More flexibility, less hardware



ELIMINATE cassettes and fan-outs

The SN<sup>®</sup> Uniboot combines four duplex SN connectors into a single compact and practical 8-fiber connector. This unique design means the SN<sup>®</sup> Uniboot supports Base-2 equipment connections and Base-8 trunk and transceiver connections simultaneously.

# TELCO-grade Optics Designed for the Data Center

- Telco grade optics with 1.25 mm zirconia ferrules
- Lower insertion loss vs MPO equivalent
- More headroom and extended reach

| er | 0 | =        |  |
|----|---|----------|--|
|    | 0 | _        |  |
|    | 0 | <u> </u> |  |
| 0  |   | 0        |  |
| 0  |   | 0        |  |
| 0  | 0 | 0        |  |
| 0  | 0 | 0        |  |

Transceivers and No-wall Adapters

**QSFP-DD** 

Shuttered and Walled Adapters

Narrow Pitch

## Wide Pitch

4CH and 2CH Available

#### FEATURES

- Fast patching with uniboot design
- Base-8 and Base-2 compatibility
- Allows up to 432 fibers per 1RU (Rack Unit)
- Provides ferrule-based alternative to MPO
- Increased flexibility and extended reach
- Significantly lower total cost of ownership
- Less complexity versus MPO
- Suitable for adapters with or without walls between ports

Direct Breakout Patent US11474315B2 and US11675137B2





**UNIBOOT CONNECTOR** 

# senko.com

\*Contact SENKO for availability

Base-8

SENKO PREEN SE

## SIMPLE. SCALABLE. SUSTAINABLE. 72f **MEGA-Density** The SN is 40% more compact than legacy LC, but nearly 3 x denser when integrated in patch panels. Up to 432 fibers can be presented in 1RU Lower Overall Cost

SN topologies require no conversion between high fiber-count trunk cables and duplex equipment ports. This means that transition cassettes and fanouts are not required

Compatible with 4CH Transceiver or


**FAST PATCHING** 400G spread in as easy as 1-2-3 Base-8 & Base-2

The SN Uniboot is so flexible that it can be used as a high-density trunk connection, a 4-lane transceiver link or as a duplex patching interface

Base-2



Compatible with 694W SN 4CH with Wall Adapter or 69D SN 4CH Shuttered Adapter



### SENKO ADVANCED COMPONENTS, INC.

#### America

USA EAST 1-888-32-SENKO USA WEST 1-858-623-3300 TEXAS 1-972-661-9080 Sales-Americas@senko.com

South America BRAZIL +55-21-3736-7065 Sales-Brazil@senko.com

#### Asia

HONG KONG +852-2121-0516 SHANGHAI +86-21-5830-4513 SHENZHEN +86-755-2533-4893 Sales-Asia@senko.com

#### Europe

FRANCE +44 7939364565 Salesfrance@senko.com GERMANY +49(0)15117683072 Sales-Germany@senko.com ITALY +39 338 8919089 Sales-Italy@senko.com POLAND +44 (0) 7796444488 Sales-Europe@senko.com

SPAIN & PORTUGAL +34 678042829 Sales-Iberia@senko.com UK +44 (0) 1256 700880 Sales-UK@senko.com OTHER +44(0) 1256 700880 Sales-Europe@senko.com

#### **CALL 1-888-32-SENKO**

**Asia Pacific** AUSTRALIA +61 (0) 3 9755-7922 Sales-Asia-Pacific@senko.com

**Middle East North Africa** DUBAI +971 4 8865160 Sales-MENA@senko.com

Japan TOKYO +81 (0) 3 5825-0911 Sales-Japan@senko.com